

毅力电子有限公司 Y.L.ELECTRONICS CO.,LTD

SMD Air Wound Coil

YLSA0908-55K



1.FEATURES

- High frequency applicatios
- Small footprint as well as low profile.
- High Q factor.
- Operating temperature range: $-40^{\circ}\text{C}\sim+125^{\circ}\text{C}$
- 100% lead (Pb) free meet RoHS Standard.

2.APPLICATIONS

- Mobile phones,wireless phones,cordless phones; PHS &2.4G applications

3.MECHANICAL DINENSIONS (UNIT:mm)



No.	A	B	C	D		
1	9.3MAX.	6.3TYP.	2.5MIN.	8.4 ± 1.0		

4.ELECTRICAL SPECIFICATION

Part Number	Inductance (uH)	Frequency Range	Rated Current (A)	Insulation (MΩ) MIN.	
YLSA0908-55K	$55.0\pm 10\%$	81MHz	22.0	10	

Storage temperature range: $-40^{\circ}\text{C}\sim+125^{\circ}\text{C}$

福建省漳州市云霄县云陵镇享堂工业区
Industrial xiang tang yun xiao town zhangzhou city fujian
province

惠州市博罗县龙溪镇电子城路46号科瑞高新产业园
Kerui High-tech Industrial Park, No.46, Yuecheng Road,
Longxi Town, Boluo County, Huizhou city, Guangdong
Province

TEL:0596-8523238 0596-8545556 FAX:0596-8523938

TEL:0752-6809969 0752-6676654 FAX:0752-6809939